

LEL SHOOTER




Certified and controlled in accordance with PPE Regulation (EU) 2016/425

Level dependance

Criterion Level	H value (dB)	M value (dB)	L value (dB)
	103.1	102.6	105.5

Effective sound pressure level



Technical Data

Average value and standard deviation of the A-weighted sound pressure level (equivalent to the diffuse sound field)

Critical band level of the test noise at the reference point	Effective level Lac (dB)					
	High test sound (Lc-La = 1.2 dB)		M test sound (Lc-La = 2.0 dB)		Low test sound (Lc-La = 6.0 dB)	
	Average value	Standard-deviation	Average value	Standard-deviation	Average value	Standard-deviation
L (dBA)	Lac (dB)	SD (dB)	Lac (dB)	SD (dB)	Lac (dB)	SD (dB)
65	67,0	4,6	68,1	4,8	67,7	4,7
70	68,2	4,6	69,5	4,7	68,9	4,8
75	69,9	4,4	71,1	4,6	70,4	4,7
80	71,5	4,2	72,7	4,4	72,2	4,4
85	73,2	3,9	74,2	4,2	73,7	4,2
90	75,1	3,4	76,0	3,9	75,5	3,9
95	77,4	2,8	77,9	3,4	77,4	3,3
100	80,1	2,3	80,2	2,7	79,8	2,6
105	83,3	2,2	82,9	2,0	82,4	1,9
110	86,9	2,2	86,2	1,5	85,6	1,2
115	91,3	2,3	90,5	1,3	90,0	1,3

Further details can be requested from the manufacturer.